RAE Systems, Inc. 1339 Moffett Park Dr.

Telephone 408-752-0723 Tube Orders 1-888-732-8823 Sunnyvale, CA 94089 USA Web www.raesystems.com

## **Gas Detection Tube Data Sheet** Ammonia NH<sub>3</sub> No. 10-100-05

	Extended Range	Standard Range	Extended Range
Range (ppmv)	0.5 - 15	1 - 30	2 - 60
No. of Pump Strokes	2	1	0.5
Sample Volume (mL)	200	100	50
Sample Time (min)	2 x 1.5	1.5	1
Correction Factor	0.55	1	2.4

Precision (Relative Standard Deviation)\*: ≤ ± 12%

Linearity with No. of Pump Strokes:  $r^2 = 0.999$ 

Humidity: The tubes are calibrated at 50% RH. @ 24 °C (75 °F)

% RH	< 5%	10%	50%	80%	95%
Corr. Factor	0.8	0.85	1.0	1.0	1.0

Temperature Range: 0 - 40°C Temp (°C/°F) 0/32 10/50 @ 50%RH (32 - 104°F)

25/77 35/95 Corr. Factor 0.9 0.95 1.0

Storage Life: 2 years in darkness at 3 - 10°C (37 - 50°F). Refrigeration required.

Color Change: Purple → Beige

Reaction Principle: 3NH<sub>3</sub> + H<sub>3</sub>PO<sub>4</sub> → (NH<sub>4</sub>)<sub>3</sub>PO<sub>4</sub>

Cross-sensitivity: Substance	Concentration (ppmv)	Apparent Reading*
Pyridine	10	15
Diethylamine	20	18
Hydrazine	20	2**
Methylhydrazine	20	2.3**
CO	100	0
CO <sub>2</sub>	20000	0#
H <sub>2</sub> S	200	0
Hexane	100	0
Isobutylene	100	0
Toluene	100	0

<sup>\*</sup> Data based on RAE pumps and tubes used in Standard range.

NH<sub>3</sub> response by 10% in mixtures, and 1000 ppm CO<sub>2</sub> has no effect.

Other Possible Interferences: Amines and other bases.

<u>Caution</u>: Dispose of spent or expired tubes according to local regulations. Possibly hazardous materials are given under the section Reaction Principle.

<sup>\*\*</sup> These hydrazines can be measured using 2 strokes with a CF of 5.

<sup># 16000</sup> ppm CO<sub>2</sub> reduces the NH<sub>3</sub> response by 30% in mixtures, 5000 ppm CO<sub>2</sub> reduces