



RAE Systems, Inc.
1339 Moffett Park Dr.
Sunnyvale, CA 94089 USA

Telephone 408-752-0723
Tube Orders 1-888-723-8823
Web www.raesystems.com

Gas Detection Tube Data Sheet

Carbon Dioxide CO₂ No. 10-104-40

| | Extended Range | Standard Range | Extended Range |
|---------------------|----------------|----------------|----------------|
| Range | 0.025 – 0.5% | 0.05 - 1% | 0.1 - 2% |
| No. of Pump Strokes | 2 | 1 | 0.5 |
| Sample Volume (mL) | 200 | 100 | 50 |
| Sample Time (min) | 2 x 2 | 2 | 1.5 |
| Correction Factor | 0.5 | 1 | 2 |

Precision (Relative Standard Deviation)*: $\leq \pm 10\%$

Linearity with No. of Pump Strokes: $r^2 = 0.994$

Humidity: No effect 5 - 85% RH

Temperature Range: 0 - 40°C
(32 - 104°F)

| Temp (°C/°F) | 0/32 | 10/50 | 21/70 | 40/104 |
|--------------|------|-------|-------|--------|
| Corr. Factor | 1.2 | 1.1 | 1.0 | 0.75 |

Storage Life: 2 years in darkness at 5 - 25°C (40 - 77°F). Refrigeration preferred.

Color Change: White → Purple

Reaction Principle: $\text{CO}_2 + \text{H}_2\text{NNH}_2 \rightarrow \text{H}_2\text{NNHCO}_2\text{H}$ (pH indicator change)

| <u>Cross-sensitivity:</u> Substance | Concentration (ppmv) | Apparent Reading* |
|--|----------------------|-------------------|
| CO | 250 | 0 |
| SO ₂ | 10 | 0.1% |
| NO | 100 | 0 |
| NH ₃ | 10% | 0 |
| CH ₄ | 2.5% | 0 |
| H ₂ S | 0.5% | 0.1% |
| Hexane | 1200 | 0 |
| Isobutylene | 100 | 0 |
| Benzene | 100 | 0 |
| Toluene | 400 | 0 |

*Data based on RAE pumps and tubes used in standard range.

Other Possible Interferences: Acid gases. Ammonia interferes in mixtures.

Note: Tube should be read immediately after exposure.

Caution: Dispose of spent or expired tubes according to local regulations.
Possibly hazardous materials are given under the section Reaction Principle.