

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/11/2015 Reviewed on 11/11/2015

1 Identification

- · Product Identifier
- · Trade name: Precision Calibration Gas Mixture
- · Product Number: G-16815
- Relevant identified uses of the substance or mixture and uses advised against: Used for calibration of gas measuring devices. Not suitable for human consumption.
- · Product Description Calibration gas mixture consisting of Methyl Mercaptan, Oxygen and Nitrogen.
- Details of the Supplier of the Safety Data Sheet:
- Manufacturer/Supplier:

Gasco Affiliates, LLC 320 Scarlett Blvd. Oldsmar, FI 34677

TELEPHONE NUMBER: (800) 910-0051

FAX NUMBER: (866) 755-8920 E-MAIL: info@gascogas.com Emergency telephone number:

Inside the US: 1-800-424-9300 (CHEMTREC, 24 hours) Outside the US: 1-703-527-3887 (CHEMTREC, 24 hours)

2 Hazard(s) Identification

· Classification of the substance or mixture:



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.

- · Label elements:
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms:



GHS04

- · Signal word: Warning
- Hazard statements:

Contains gas under pressure; may explode if heated.

Precautionary statements:

Protect from sunlight. Store in a well-ventilated place.

- Classification system:
- · NFPA ratings (scale 0 4)



Health = 0 Fire = 0 Reactivity = 0

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/11/2015 Reviewed on 11/11/2015

Trade name: Precision Calibration Gas Mixture

HMIS-ratings (scale 0 - 4)



· Hazard(s) not otherwise classified (HNOC): None known

3 Composition/Information on Ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous Components:		
CAS: 74-93-1 RTECS: PB 4375000	Methyl Mercaptan Flam. Gas 1, H220; Flam. Liq. 1, H224; Acute Tox. 3, H331; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Press. Gas, H280	0.0005-0.005%
CAS: 7782-44-7	Oxygen ♦ Oxid. Gas 1, H270; ♦ Press. Gas, H280	20-21%
CAS: 7727-37-9 RTECS: QW 9700000	Nitrogen ♦ Press. Gas, H280; Simple Asphyxiant	78.995-79.9995%

4 First-Aid Measures

- · Description of first aid measures:
- · General information:

Symptoms may even occur after several hours; therefore observe area effected for at least 48 hours after the accident.

· After inhalation:

Generally the product does not irritate with inhalation.

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Generally the product does not irritate the skin.

In cases of contact with liquified material, frostbite may occur. Immerse frostbite in cool-warm water and seek medical attention.

Wash with soap and water.

If skin irritation occurs, consult a doctor.

· After eye contact:

Not anticipated under normal use.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Not a normal route of entry.

If swallowed and symptoms occur, consult a doctor.

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

(Contd. on page 3)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/11/2015 Reviewed on 11/11/2015

Trade name: Precision Calibration Gas Mixture

5 Fire-Fighting Measures

· Extinguishing media:

Suitable extinguishing agents:

Use fire fighting measures that suit the environment.

Use water spray to cool fire-exposed containers.

· Special hazards arising from the substance or mixture:

Closed containers may explode when exposed to extreme heat.

If incinerated, product will releaset the following toxic fumes: Oxides of Carbon, Nitrogen (NOx) and Sulfur.

Advice for firefighters:

This gas mixture is not flammable; however, containers, when involved in fire, may rupture or burst in the heat of the fire.

Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures

· Personal precautions, protective equipment and emergency procedures:

Treat any fumes as toxic.

Ensure adequate ventilation.

Keep people at a distance and stay upwind.

In a confined area, NIOSH approved respiratory protection may be required.

- Environmental precautions: Inform authorities in case of gas release.
- · Methods and material for containment and cleaning up:

Dispose of the collected material according to regulations.

Ensure adequate ventilation.

Dispose contaminated material as waste according to section 13.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- Handling
- · Precautions for safe handling: Ensure good ventilation/exhaustion at the workplace.
- · Information about protection against explosions and fires:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Do not cut, grind or weld on container that contains or contained product.

Do not spray on a naked flame or any incandescent material.

· Conditions for safe storage, including any incompatibilities:

Store away from strong oxidizing agents, phosphorus, organic materials and powdered metals.

· Storage

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Cylinders should be firmly secured to prevent falling or being knocked over. Cylinders must be protected from the environment, and preferably kept at room temperature. Cylinders should be stored in dry, well-ventilated areas, away from sources of heat, ignition, and direct sunlight. Protect cylinders against physical damage. Full and empty cylinders should be segregated. Use a "first-on, first-out" inventory system to prevent full containers from being stored for long periods of time.

· Information about storage in one common storage facility: Not required.

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/11/2015 Reviewed on 11/11/2015

Trade name: Precision Calibration Gas Mixture

- · Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · Specific end use(s): No further relevant information available.

8 Exposure Controls/Personal Protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters:

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

· Components with occupational exposure limits:

7727-37-9 Nitrogen

TLV withdrawn TLV, see App. F; simple asphyxiant

74-93-1 Methyl Mercaptan

PEL Ceiling limit value: 20 mg/m³, 10 ppm REL Ceiling limit value: 1* mg/m³, 0.5* ppm

*15-min

TLV Long-term value: 0.98 mg/m³, 0.5 ppm

- · Additional information: The lists that were valid during the creation of this SDS were used as basis.
- · Exposure controls:
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

· Breathing equipment:



Suitable respiratory protective device recommended.

- · Protection of hands: Not required.
- · Material of gloves: Not required.
- · Penetration time of glove material: Not applicable.
- · Eye protection: Not required.
- · Body protection: Not required.

9 Physical and Chemical Properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Gaseous Clear, colorless

· Odor: Rotten

Odor threshold: Not determined.pH-value: Not determined.

Change in condition

Melting point/Melting range: Not determined.

(Contd. on page 5)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/11/2015 Reviewed on 11/11/2015

Trade name: Precision Calibration Gas Mixture

Boiling point/Boiling range: Not determined.

· Flash point: None

Flammability (solid, gaseous): Not determined.
 Ignition temperature: Not determined
 Decomposition temperature: Not determined.

· Auto igniting: Product is not self-igniting.

· Danger of explosion: Not determined.

· Explosion limits:

Lower: Not determined.

Upper: Not determined.

Vapor pressure: Not determined.

· Density:

Relative density:

Vapor density:

Not determined.

Not determined.

Evaporation rate:

Not applicable.

· Solubility in / Miscibility with:

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

Other information: No further relevant information available.

10 Stability and Reactivity

- · Reactivity: No further relevant information available.
- · Chemical stability: Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials: Strong oxidizing agents, phosphorus, organic materials and powdered metals.
- · Hazardous decomposition products: Carbon Oxides, Nitrogen Oxides and Sulfur Oxides.

11 Toxicological Information

- Information on toxicological effects:
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

74-93-1 Methyl Mercaptan

Inhalative LC50/4 h 13.0 mg/l (mouse)

- Primary irritant effect:
- · On the skin: No irritating effect.
- · On the eye: No irritating effect.

(Contd. on page 6)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/11/2015 Reviewed on 11/11/2015

Trade name: Precision Calibration Gas Mixture

- Additional toxicological information:
- Carcinogenic categories:
- IARC (International Agency for Research on Cancer):
- Group 1 Carcinogenic to humans
- Group 2A Probably carcinogenic to humans
- Group 2B Possibly carcinogenic to humans
- Group 3 Not classifiable as to its carcinogenicity to humans
- Group 4 Probably not carcinogenic to humans

None of the ingredients are listed.

NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

2 Ecological Information

- · Toxicity: The hazards for the aquatic environment are unknown.
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- · Mobility in soil: No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment:
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects: No further relevant information available.

3 Disposal Considerations

- · Waste treatment methods:
- Recommendation:

Observe all federal, state and local environmental regulations when disposing of this material.

Release all residual gas pressure in a well ventilated area. Verify the cylinder is completely empty (0 PSIG). Remove or cover any hazard labels. Return empty cylinder for recycling.

NOTE: Check with the local easte authority before placing any gas cylinder into waste container for pickup. GASCO encourages the consumer to return all cylinders.

UN1956

· Waste disposal kev:

The U.S. EPA has not published waste disposal numbers for this product's components.

- · Uncleaned packagings:
- · **Recommendation:** Return cylinder and unused product to supplier.

4 Transport Information

- · UN-Number:
- · DOT, ADR, IMDG, IATA

· UN proper shipping name:

· DOT, IATA Compressed gas, n.o.s.

· ADR UN1956 Compressed gas, n.o.s.

(Contd. on page 7)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/11/2015 Reviewed on 11/11/2015

Trade name: Precision Calibration Gas Mixture

· **IMDG** COMPRESSED GAS, N.O.S.

Transport hazard class(es):

· DOT



· Class: 2.2 · Label: 2.2

· ADR



· Class: 2.2 1A · Label: 2.2

· IMDG, IATA



· Class: 2.2 · Label: 2.2

· Packing group:

· **DOT, ADR, IMDG, IATA** Non-Regulated Material

Environmental hazards:
 Special precautions for user:
 Danger code (Kemler):

Not applicable.
20

• EMS Number: F-C,S-V
• Stowage Category A

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code: Not applicable.

· Transport/Additional information:

· DOT

• **Quantity limitations:**On passenger aircraft/rail: 75 kg
On cargo aircraft only: 150 kg

· ADR

· Excepted quantities (EQ): Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· IMDG

Limited quantities (LQ):
 Excepted quantities (EQ):
 Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 1956 COMPRESSED GAS, N.O.S., 2.2

(Contd. on page 8)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/11/2015 Reviewed on 11/11/2015

Trade name: Precision Calibration Gas Mixture

15 Regulatory Information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture:
- SARA (Superfund Amendments and Reauthorization):
- · Section 355 (extremely hazardous substances):

74-93-1 Methyl Mercaptan

Section 313 (Specific toxic chemical listings):

74-93-1 Methyl Mercaptan

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · California Proposition 65:
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

- · Carcinogenic categories:
- EPA (Environmental Protection Agency):

None of the ingredients are listed.

TLV (Threshold Limit Value established by ACGIH):

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health):

None of the ingredients are listed.

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



GHS04

- · Signal word: Warning
- Hazard statements:

Contains gas under pressure; may explode if heated.

Precautionary statements:

Protect from sunlight. Store in a well-ventilated place.

National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

(Contd. on page 9)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/11/2015 Reviewed on 11/11/2015

Trade name: Precision Calibration Gas Mixture

· State Right to Know:			
CAS: 7727-37-9 RTECS: QW 9700000	Nitrogen ♦ Press. Gas, H280; Simple Asphyxiant	78.995-79.9995%	
CAS: 7782-44-7	Oxygen ♦ Oxid. Gas 1, H270; ♦ Press. Gas, H280	20-21%	
CAS: 74-93-1 RTECS: PB 4375000	Methyl Mercaptan ♦ Flam. Gas 1, H220; Flam. Liq. 1, H224; ♦ Acute Tox. 3, H331; ♦ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Press. Gas, H280	0.0005-0.005%	
All ingredients are listed.			

[·] Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

* 16 Other Information

· Relevant phrases:

Gasco Affiliates, LLC, makes not express or implied warranties, guarantees or representations regarding the product of the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Gasco Affilitates, LLC shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use of reliance upon the information herein.

· Date of preparation / last revision: 11/11/2015 / -

· Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Gas 1: Flammable gases, Hazard Category 1

Oxid. Gas 1: Oxidising Gases, Hazard Category 1

Press. Gas: Gases under pressure: Compressed gas

Flam. Liq. 1: Flammable liquids, Hazard Category 1

Acute Tox. 3: Acute toxicity, Hazard Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106